

SAFETY DATA SHEET

VOLTRONIC ANTI-SEIZE-SPRAY IX10

Page 1

Issued: 21.09.2009

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: VOLTRONIC ANTI-SEIZE-SPRAY IX10

Product code: IX10

Synonyms: ALUPASTENSPRAY

Use of substance / preparation: Lubricant Aerosol

Company name: VOLTRONIC & ACT GmbH

Weidenweg 12

Bad Boll

D-73087

Germany

Tel: +49 7164 4016

Fax: +49 7164 5994

Emergency tel: +49 7164 4016

Email: info@voltronic-germany.com

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive dust-air mixture. Harmful if swallowed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PROPAN/BUTAN 50-70%

CAS: 68131-75-9

[F+] R12

- LOW BOILING POINT HYDROGEN TREATED NAPHTA, LIGHT (C6-C8) 10-30%

EINECS: 265-151-9 CAS: 64742-49-0

[F] R11; [Xi] R38; [N] R51/53; [Xn] R65

4. FIRST AID MEASURES (SYMPTOMS)

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET

VOLTRONIC ANTI-SEIZE-SPRAY IX10

Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Mix with sand or vermiculite.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Ensure lighting and electrical equipment are not a source of ignition. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: PROPAN/BUTAN
WEL (8 hr TWA): 1000 WEL (15 min STEL): 4

- LOW BOILING POINT HYDROGEN TREATED NAPHTA, LIGHT (C6-C8)
WEL (8 hr TWA): 1000 mg/m³ (200ppm)

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves. Breakthrough time of the glove material > 4 hours.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Silver

Odour: Characteristic odour

Solubility in water: Insoluble

Viscosity: Non-viscous

Flammability limits %: lower: 0,6

upper: 11,0

Flash point°C: <-5

Autoflammability°C: >250

Vapour pressure: 3,5b/20°C;7b/50°C**Relative density:** 0,68**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Sources of ignition.**Materials to avoid:** Strong oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****12. ECOLOGICAL INFORMATION****Mobility:** Non-volatile.**Persistence and degradability:** Only slightly biodegradable.**Bioaccumulative potential:** Bioaccumulation potential.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D9 Physico-chemical treatment not specified elsewhere in this Annex which results in final compounds or mixtures which are disposed of by means of any of the operations in this Annex (e.g. evaporation, drying, calcination, etc.).

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5F**Shipping name:** AEROSOLS (PROPAN/BUTAN; LOW BOILING POINT HYDROGEN TREATED NAPHTA, LIGHT)**Labelling:** 2.1**IMDG / IMO****UN no:** 1950**Class:** 2

SAFETY DATA SHEET
VOLTRONIC ANTI-SEIZE-SPRAY IX10**EmS:** F-D,S-U**Marine pollutant:** .**Labelling:** 2.1**IATA / ICAO****UN no:** 1950**Class:** 2**Labelling:** 2.1**15. REGULATORY INFORMATION****Hazard symbols:** Extremely flammable.**Risk phrases:** R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S60: This material and its container must be disposed of as hazardous waste.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Haz. ingredients (label): LOW BOILING POINT HYDROGEN TREATED NAPHTA, LIGHT**Water hazard class:** 2 Classification by VwVwS**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Risk phrases used in s.3:** R12: Extremely flammable.

R11: Highly flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

SAFETY DATA SHEET
VOLTRONIC ANTI-SEIZE-SPRAY IX10

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.