

SAFETY DATA SHEET
VOLTRONIC UNIVERSAL SPRAY IX22

Page 1
Issued: 22.09.2009
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: VOLTRONIC UNIVERSAL SPRAY IX22

Product code: IX22

Use of substance / preparation: Cleaner Lubricant Contactspray corrosion prevention Protector Aerosol liquid

Company name: VOLTRONIC & ACT GmbH

Weidenweg 12

Bad Boll

D-73087

Germany

Tel: +49 7164 4016

Fax: +49 7164 5994

Emergency tel: +49 7164 4016

Email: info@voltronic-germany.com

2. HAZARDS IDENTIFICATION

Main hazards: Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTA C10- C12 >90%

[Xn] R65; [-] R66

- KOHLENDIOXYD (CO²) 1-10%

EINECS: 2046969 CAS: 00124-38-9

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: May cause dizziness.

Inhalation: Drowsiness or mental confusion may occur. There may be vomiting.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. Transfer to hospital as soon as possible.

Inhalation: If unconscious and breathing is OK, place in the recovery position. Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside keep bystanders upwind and away from danger point.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Mix with sand or vermiculite. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep away from direct sunlight. The floor of the storage room must be impermeable to prevent the escape of liquids. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTA C10- C12
WEL (8 hr TWA): 200 ml/m³ 1000mg/m³ WEL (15 min STEL): Kat.4

- KOHLENDIOXYD (CO²)
WEL (8 hr TWA): 5000 ppm

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. Ensure storage room has retention walls. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protective device with particle filter. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves. Breakthrough time of the glove material > 4 hours.

Eye protection: Safety goggles.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Yellow-tan

Odour: Characteristic odour

SAFETY DATA SHEET
VOLTRONIC UNIVERSAL SPRAY IX22**Evaporation rate:** Moderate**Solubility in water:** Slightly soluble**Also soluble in:** Most organic solvents.**Viscosity:** Non-viscous**Viscosity value:** 1,6**Viscosity test method:** Kinematic viscosity in 10-6 m²/s at 40°C (ISO 3104/3105)**Boiling point/range°C:** 185-285**Flammability limits %: lower:** 1,0**upper:** 7,4**Flash point°C:** 63**Autoflammability°C:** 230**Vapour pressure:** 6,0bar/20°C;9,0/50°C**Relative density:** 0,78**VOC g/l:** 757**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Flames. Sources of ignition.**Materials to avoid:** Strong oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****12. ECOLOGICAL INFORMATION****Mobility:** Floats on water.**Persistence and degradability:** Biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D9 Physico-chemical treatment not specified elsewhere in this Annex which results in final compounds or mixtures which are disposed of by means of any of the operations in this Annex (e.g. evaporation, drying, calcination, etc.).

R1 Solvent reclamation/regeneration.

Disposal of packaging: Burn in a chemical incinerator equipped with afterburners and scrubbers. Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION**

ADR / RID

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS (KOHLENDIOXYD (CO₂); HYDROCARBONS, DEAROMAT.)
Labelling: 2.1



IMDG / IMO

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Symbol not required.

Risk phrases: R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Haz. ingredients (label): LOW BOILING POINT HYDROGEN TREATED NAPHTHA C10- C12

Water hazard class: 1 Classification by VwVwS

Air emission directive: Class: III Amount m%: 80

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.